

- vi serverar
hantverkare!

Laseal – window sealant

It is important to use a window sealant that is elastic and does not dry out or crack, especially when applying sealants on large window frames without mullions. The durability of the window depends on the fact that the sealant is impenetrable between the glas and wood frame. If the sealant is impenetrable the colour and the wood will last longer and the need for maintenance will be less frequent.

Laseal, is produced to have the right "texture" so that it will be easy to apply when using a sealant gun. You do not need to paint over the sealant if you do not want to, but the product can be painted after 10 minutes of applying it to the surface, you can use most generic clearcole for windows, even linseed oil paint. Laseal is a modern window putty that contains all the good qualities in one product.



- Good aging qualities
- Elastic with great adhesiveness
- Silicone free
- Contains no solvents
- Available in several colours
- Can be painted using most generic clearcole
- Can be used to fix old linseed putty
- Used by leading windowtreatment, glaziers companies and window producers

10 years material-guarantee

We guarantee that Laseal from the application date keeps its sealing qualities as a window sealant for single glazing against glas and wood for 10 years. For more information see www.leifarvidsson.se.

Egenskaper	Laseal
Mold resistant	Yes
Temperature resistance °C	-40/+90
Skin formation	ca 20 min
Joint movement	+/-25%
Tensile strength N/mm ²	1,1
Elongation at break	245%
Hardness, Shore A	35
Storage time	12 months



SEE THE MOVIE!
www.leifarvidsson.se

PRODUCTSHEET 2020



LEIF ARVIDSSON AB

MULLSJÖ

Tel 0392-360 10

Box 90, 565 22 MULLSJÖ

VISIT THE WEBSHOP – www.leifarvidsson.se